



HOW TO APPLY WOOD BUTTER

MATERIALS NEEDED

- tmbr Wood Butter
- Clean lint-free cloth
- Soft buffing cloth
- Disposable gloves (optional)

STEP 1: CLEAN THE SURFACE

1. Ensure the wood is clean, dry, and free of dust or debris.
2. Lightly sand rough areas if necessary and remove all dust.

STEP 2: APPLY THE WOOD BUTTER

3. Using a clean cloth, apply a small amount of wood butter to the surface.
4. Rub it in using circular motions or follow the wood grain.
5. Cover the entire surface evenly.

STEP 3: ALLOW ABSORPTION

6. Let the wood butter soak into the wood for 30 to 45 minutes.
7. Dry wood may absorb more product and may require an additional application.

STEP 4: WIPE OFF EXCESS

8. Use a clean cloth to remove any excess product that remains on the surface.
9. The finish should feel smooth rather than greasy.



STEP 5: BUFF THE SURFACE

10. Buff the wood with a soft cloth to achieve a clean, even sheen.
11. Continue buffing until the desired appearance is reached.

Step 6: Maintain as Needed

12. Reapply periodically or whenever the wood appears dry or dull.
13. Food-contact items such as cutting boards may require more frequent maintenance.

TIPS FOR BEST RESULTS

- Apply thin, even coats rather than heavy applications.
- Allow the product sufficient time to penetrate the wood.
- Store wood butter in a cool place.
- Wood Butter can be warmed up slightly to assist spreading.
- Test on a small hidden area before treating valuable items.
- Regular maintenance helps keep wood hydrated and protected.